



INLAY

DEPOSITION AID

PRINCIPAL FUNCTIONING AGENTS

Lubricating oils (petroleum), hydrotreated spent; oleic acid, polyethylene glycol undecyl ether	99.2%
Constituents ineffective as an adjuvant	0.8%
Total	

^{*}Contains petroleum distillates. All ingredients are exempt from tolerance under 40 CFR 180. WA Reg. No. 52467-20002

KEEP OUT OF REACH OF CHILDREN CAUTION

PRECAUTIONARY STATEMENT

Read label before use. Keep container tightly closed. Keep only in original container. Do not eat, drink or smoke when using this product. Avoid breathing spray. Wash hands thoroughly after handling.

FIRST AID

Have the product container with you if calling a poison control center or doctor, or going for treatment.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do then continue rinsing.

IF ON SKIN OR CLOTHING: Take off contaminated clothing and wash it before reuse. Wash with plenty of soap and water.

IF SWALLOWED: Unless advised otherwise by a poison control center or doctor, have person rinse mouth with water, if able. Do not give anything by mouth to an unconscious person. Do not induce vomiting.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If person is not breathing, call 911 or an ambulance.

PERSONAL PROTECTIVE EQUIPMENT: Wear chemical protective gloves, protective clothing, and eye protection.

NET CONTENTS: 2.5 U.S. Gallons (9.46 L)



GENERAL INFORMATION

INLAY^m is formulated with a superior surfactant system and paraffinic oil to improve deposition and penetration of the active ingredient into the target surface.

INLAY promotes efficacy by increasing soil adsorption which can help to reduce run-off and leaching of the spray application.

NOT FOR AQUATIC USE.

DIRECTIONS FOR USE

Follow the instructions on the most restrictive active ingredient label.

Tank mixtures should only be applied within the label recommendations of every product in the tank mixture.

Order of addition

Prior to mixing, fill the spray tank with half of the carrier. Start the sprayer and check to make sure that all valves and gauges work and that there is adequate tank agitation.

In general, follow the W-A-L-E-S plan when adding herbicides to a tank mix.

- 1. Wettable Powders (WP) then Flowables (F, DF)
- 2. Agitate then add anti-foaming compounds or buffers.
- 3. Liquid and Soluble products
- 4. Emulsifiable concentrates (EC)

5. INLAY

Caution should be used when applying this or any other product on plants during hot, dry conditions.

Though phytotoxicity has been evaluated, care should be taken by conducting a jar test or testing this product on sensitive plants before full application is performed.

APPLICATION RATES

Application rate of tank mix by air or ground (gallons per acre)	Application rate of INLAY per acre
0-5	6 to 16 ounces*
5-30	1 to 4 pints
Above 30	1% minimum in spray mix

^{*}Ensure 1% minimum is added to the spray tank but do not exceed 5%.

Small volume equipment: 0.5 to 1 ounce per gallon of solution.

STORAGE AND DISPOSAL

Storage: Store in a cool well-ventilated place. Keep in original container tightly closed. Do not reuse empty container. Do not store with food, feed, or other material to be used or consumed by humans or animals. Do not contaminate water supplies. STORE BETWEEN 40° AND 90° F.

Disposal: Do not contaminate water, food or feed by disposal. Dispose of contents in container to an approved waste disposal facility in accordance with all local, regional, national and international regulations. Triple rinse (or equivalent) adding rinse water to application tank. Offer container for recycling or dispose of in a sanitary landfill or by other procedures approved by local regulations. The Agricultural Container Recycling Council (ACRC) operates the national recycling program. To contact your state and local ACRC recycler visit the ACRC web page at www.acrecycle.org.

WARRANTY STATEMENT: EXACTO®, INC. (Exacto) represents and warrants that its products are manufactured in accordance with the product's specifications and that its products, at the time of delivery to the purchaser, shall be free from all material defects. EXACTO MAKES NO WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE DISCLAIMED. FURTHER, IT IS UNDERSTOOD AND AGREED THAT EXACTOS' LIABILITY SHALL NOT EXCEED THE RETURN OF THE AMOUNT OF THE PURCHASE PRICE PAID BY PURCHASER AND UNDER NO CIRCUMSTANCES SHALL EXACTO BE LIABLE FOR SPECIAL, INDIRECT, INCIDENTAL, CONSEQUENTIAL OR PUNITIVE DAMAGES. Products for which a warranty claim is made are to be returned transportation prepaid to Exacto's production facility. Any use not in accordance with product directions and precautionary statements, and any modifications or additives to the products, or any adulteration, dilution or alteration by the purchaser shall used this warranty in any way or to grant any other warranty. No employee or representative of Exacto is authorized to change this warranty in any way or to grant any other warranty.